



Z-TRONIK Fiber Optic Splice Closure



GPJM3-RS provide with four fiber cable in-out ports (3 round ports, 1 elliptical port), it can be used in aerial and underground application, it is made from quality engineering plastic, the cover and the base are filled with silicon rubber and sealed with hoop, then entry ports are sealed with thread parts, it can be opened after sealing and can be reused without changing sealing material.

(Available for aerial and underground)

Item	GPJM3-RS
Dimension (MM)	φ 190x435
Weight (kg)	
Cable diameter (MM)	φ 7 – φ22
Cable entry ports	Four
Max Capacity of Fiber Splice	12(single)/24(single)
Max Capacity of Splice Tray	4
Max Capacity	48(12/ single 12fibres/tray) 96(24/ single 24fibres/tray)
Structure of cable entry port	Heat-shrinkable sealing structure
Sealing structure	Silicon gum material



Description	Type	Quantity
Splice protector tube		According to the fiber cores
Fiber protector tube		According to the splice tray
Marking note		1 piece
Abrasive cloth		1 piece
Cables ties		4 x splice tray
Metal hoop		1 set
Plastic hoop		1 set
Branching card		1 piece
Heat-shrinkable tube	φ 32x150	3PCS
Heat-shrinkable tube	φ 63x150	1 piece

Inner carton dimension mm	Inner carton weight kg	Outside carton dimension mm	Outside carton weight kg	No. of units per carton PCS
445 x 170 x 205	2.25	550 x 450 x 480	15	6